

Specifications

Span width:

3.00m

Eave Height:

2.50m

Ridge height:

3.12m

Peak height:

5.10m

Bay distance:

3.00m

Roof pitch:

20°

No of gable uprights:

0

Longest component (m):

2.90m

Minimum length:

3.00 m

Maximum length:

Multiple configurations possible

Snow loading compliance:

N/A

Max allowed wind speed to DIN:

80 km/h (0.30kN/m²)

Main profile size:

63/63/2mm (3 channel)

Eave connection type:

Internal Galvanised Steel Insert

Aluminium type:



European - Hard Pressed Extruded Structural Aluminium

Connecting components:

European - hot dipped, structural grade corrosive resistant galvanised steel

Textile roof and wall covering:

Premium grade, high gloss white, PVC coated polyester fabric - UV resistant and flame retardant according to: DIN 4102 B1, M2; BS 5438/7837; USA NFPA701.



Accessories Available

- ▶ 40 / 60 / 80 / 100mm Insulated composite walling
- ▶ Integrated cassette ISO / hard walling system.
- ▶ Overhead door canopies
- ▶ Georgian or Clear PVC window walls
- ▶ Internal & external access ramps
- ▶ Premium double door units
- ▶ Integrated cassette ABS / hard walling system.
- ▶ Internal flat or pleated linings
- ▶ More accessories are available...



SKIPPY-RENT[®]EVENTS[®]

Evenementenservice

www.skippy-rent.nl

Specifications

Span width:

4.00m

Eave Height:

2.50m

Ridge height:

3.38m

Peak height:

5.47m

Bay distance:

4.00m

Roof pitch:

20°

No of gable uprights:

0

Longest component (m):

3.90m

Minimum length:

4.00 m

Maximum length:

Multiple configurations possible

Snow loading compliance:

N/A

Max allowed wind speed to DIN:

80 km/h (0.30kN/m²)

Main profile size:

63/63/2mm (3 channel)

Eave connection type:

Internal Galvanised Steel Insert

Aluminium type:



European - Hard Pressed Extruded Structural Aluminium

Connecting components:

European - hot dipped, structural grade corrosive resistant galvanised steel

Textile roof and wall covering:

Premium grade, high gloss white, PVC coated polyester fabric - UV resistant and flame retardant according to: DIN 4102 B1, M2; BS 5438/7837; USA NFPA701.



Accessories Available

- ▶ 40 / 60 / 80 / 100mm Insulated composite walling
- ▶ Integrated cassette ISO / hard walling system.
- ▶ Overhead door canopies
- ▶ Georgian or Clear PVC window walls
- ▶ Internal & external access ramps
- ▶ Premium double door units
- ▶ Integrated cassette ABS / hard walling system.
- ▶ Internal flat or pleated linings
- ▶ More accessories are available...



SKIPPY-RENT[®]EVENTS[®]

Evenementenservice

www.skippy-rent.nl

Specifications

Span width:

5.00m

Eave Height:

2.50m

Ridge height:

3.64m

Peak height:

5.72m

Bay distance:

5.00m

Roof pitch:

20°

No of gable uprights:

0

Longest component (m):

4.90m

Minimum length:

5.00 m

Maximum length:

Multiple configurations possible

Snow loading compliance:

N/a

Max allowed wind speed to DIN:

80 km/h (0.30kN/m²)

Main profile size:

63/63/2mm (3 channel)

Eave connection type:

Internal Galvanised Steel Insert

Aluminium type:



European - Hard Pressed Extruded Structural Aluminium

Connecting components:

European - hot dipped, structural grade corrosive resistant galvanised steel

Textile roof and wall covering:

Premium grade, high gloss white, PVC coated polyester fabric - UV resistant and flame retardant according to: DIN 4102 B1, M2; BS 5438/7837; USA NFPA701.



Accessories Available

- ▶ 40 / 60 / 80 / 100mm Insulated composite walling
- ▶ Integrated cassette ISO / hard walling system.
- ▶ Overhead door canopies
- ▶ Georgian or Clear PVC window walls
- ▶ Internal & external access ramps
- ▶ Premium double door units
- ▶ Integrated cassette ABS / hard walling system.
- ▶ Internal flat or pleated linings
- ▶ More accessories are available...



SKIPPY-RENTEVENTS®

Evenementenservice

www.skippy-rent.nl